








MT15 H110

Client



- ✓ Ideal in all home & office contexts.
- ✓ 7th generation Intel® Core™ processor
- ✓ Intel® HD graphics with up to 2 simultaneous displays
- ✓ Support for dedicated PCI Express 3.0 x16 video cards
- ✓ Built-in High Definition Audio 2/4/5.1/7.1-channel



MT15 H110

Client



System	Processor	7 th / 6 th Generation Intel® Core™ Processors Socket LGA 1151 Intel® Core™ i7 / i5 / i3, Pentium
	Chipset	Intel® H110 Express Chipset
	BIOS	1 x 64Mbit flash, AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
	Expansion Slots	1 x PCI Express 3.0 x16 2 x PCI Express 2.0 x1
Memory	Max Exp.	32GB
	Type	DDR4-2400/2133 UDIMM 288pin 4GB, 8GB, 16GB
	Slot	2
Front I/O interfaces	Audio	1 x Jack 3.5mm headphone 1 x Jack 3.5mm microphone
	USB	2 x USB 2.0 (optional 3.0)
	Back I/O interfaces	Serial 1 x RS232 optional
Back I/O interfaces	LPT	1 x N/A
	USB	4 x USB 2.0
		2 x USB 3.0
		2 x USB 2.0 optional 2 x USB 3.0 optional
	Keyboard /Mouse	2 x PS/2
	Audio	3 x Jack 3.5mm (Line In, Line Out, Mic In)
	LAN	1 x RJ45
	Video	1 x VGA DB15
		1 x DVI-D
		1 x HDMI
Storage	Integrated storage controller	4 x SATA3 6Gb/s
	Card Reader	Opzionale
	HDD/SSD bay	4 x *HDD/SSD SATA 2.5" or 3.5"
	ODD bay	3 x *DVD +R+RW-R-RW
	Note	*Check web configurator for the base model installed and available options
	Video subsystem	Integrated graphics adapter
Maximum resolution		VGA DB15 : 1920x1200@60 Hz DVI-D : 1920x1200@60 Hz HDMI 1.4 : 4096x2160@24 Hz
Simultaneous active displays		Up to 2
Dedicated graphics adapter		Check web configurator for the available options or request a custom option

Audio subsystem	Integrated audio adapter	Intel® HD Audio (codec Realtek® ALC887)
	Channel	2 / 4 / 5.1 / 7.1 channel The HDMI 1.4 port also delivers the audio signal
Network subsystem	Integrated LAN adapter	1 x Realtek® GbE LAN chip (10/100/1000 Mbit)
	Power	Standard power supply 350W ATX ACTIVE PFC, 80Plus Bronze (85+) AC INPUT:200-240V, 2.5A, 50-60Hz
Mechanical features	L x H x D	180mm x 425mm x 480mm
	Weight	9 Kg for medium configuration
	Internal bay	4 x 3 ¹ / ₂ unit
	External bay	3 x 5 ¹ / ₄ unit 1 x 3 ¹ / ₂ unit
Software	Colour	Black
	Supported operating system	Microsoft Windows 7 64bit only with 6 th gen. cpu. Microsoft Windows 8.1 64bit only with 6 th gen. cpu. Microsoft Windows 10 64bit
Environment	Operating temp.	From +5°C to +35°C
	Non operating temp.	From -20°C to +70°C
	RH	95% @ 30°C non cond.
Product certifications	Reference Marks	CE, RoHS
	Directive	Built according to EU Directive 2014/30/EU(EMCD), 2014/35/EU(LVD) and 2011/65/EU(RoHS)
Company certifications	Reference standards	UNI EN ISO 9001
Product code	CNMD95MRIN0	MT15 Intel H110, DDR4, Gb Lan+SATA3, USB 2.0/3.0



www.intercomp.it

Intercomp S.p.A.
Via della Scienza 27
37139, Verona, Italia
Tel +39 045-8378411
Fax +39 045-8510539



ISO 9001:2008

intercomp@intercomp.it

Il prodotto potrebbe differire dalle immagini riportate. Tutti i nomi e marchi registrati sono dei legittimi proprietari. Tutte le caratteristiche e specifiche potranno essere modificate senza alcun preavviso.
Aggiornato il 01/06/2017