














CORA 4000 C232

Action Graphics



- ✓ Ideal for rack mount systems where graphics processing is relevant.
- ✓ Intel® Xeon® E3-1200 v6 & v5 or 7th & 6th gen. Intel® Core™ processor
- ✓ Dual Channel ECC or Un-buffered DDR4 memory
- ✓ Support for dedicated PCI Express 3.0 x16 video cards
- ✓ Built-in Intel® RAID 6-channel SATA Controller, up to 6Gb/s
- ✓ Ultra-Fast M.2 with PCIe NVMe x4 & SATA interface
- ✓ Built-in High Definition Audio 2/4/5.1/7.1-channel



 <p>Intel® Xeon® E3-1200 v6</p>	 <p>Kaby Lake CPU 7th Gen Intel® Core™</p>	 <p>DDR4 ECC UP TO 64 GB</p>	 <p>Multi Graphics Video Card PCI EXPRESS 3.0</p>	 <p>M.2 STORAGE PCIe NVMe</p>	 <p>Integrated SATA RAID CTRL RAID 0, 1, 5, 10</p>	 <p>USB 3.0</p>
<p>RACKMOUNT 19" ↔ 4U ↑↓</p>	 <p>LAN Gb LAN</p>	 <p>COM RS232</p>	 <p>DVD ReWritable</p>	 <p>+5~+35°C</p>	 <p>RoHS</p>	 <p>CE</p>

CORA 4000 C232

Action Graphics



System	Processor	Intel® Xeon® E3-1200v6 or v5 Intel® Core™ 7 th or 6 th gen. Processor socket LGA 1151	
	Chipset	Intel® C232 Chipset	
	BIOS	2 x 64Mbit flash AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0	
	Expansion Slots	1 x PCI Express 3.0 x16	
		1 x PCI Express 3.0 x4 (mechanical x16) Note. Support for 2-Way CrossFireX™ 2 x PCI 32bit 5V	
Memory	Max Exp.	64GB	
	Slot	4 x DIMM 288pin	
	Max size per slot	4GB, 8GB, 16GB	
	Type	With Xeon® CPU: ECC DDR4-2400/2133 With Core™ CPU: Unbuffered DDR4-2400/2133	
Front I/O interfaces	Audio	1 x Jack 3.5mm headphone 1 x Jack 3.5mm microphone	
	USB	2 x USB 2.0	
Back I/O interfaces	USB	2 x USB 2.0 4 x USB 3.0 4 x USB 2.0 optional 2 x USB 3.0 optional	
	Serial	1 x RS232 optional	
	LPT	1 x LPT optional	
	Keyboard /Mouse	2 x PS/2	
	Audio	6 x Jack 3.5mm	
	LAN	1 x RJ45	
	Video	Depends on selected (optional) PCIe video card.	
	Storage	Integrated storage controller	1 x M.2 (Socket 3, M key, 2242/2260/2280 SATA or PCIe x4) 1 x SATA Express (not compatible with regular SATA devices) 6 x SATA3 6Gb/s Support for RAID 0, 1, 5, 10
		Card Reader	Opzionale
		HDD/SSD bay	2 x *HDD/SSD SATA 2.5" or 3.5"
ODD bay		3 x *DVD +R+RW-R-RW	
Note		*Check web configurator for the base model installed and available options	
Video subsystem		Integrated graphics adapter	N/A
	Maximum resolution	Depends on selected (optional) PCIe video card.	
	Simultaneous active displays	Depends on selected (optional) PCIe video card.	
	Dedicated graphics adapter	Check web configurator for the available options or request a custom option.	

Audio subsystem	Integrated audio adapter	Intel® HD Audio (codec Realtek® ALC892)
	Channel	2 / 4 / 5.1 / 7.1 channel
Network subsystem	Integrated LAN adapter	1 x Intel® GbE LAN chip (10/100/1000 Mbit)
	Power	Standard power supply 700W ATX ACTIVE PFC, 80Plus Bronze (85+) AC INPUT:200-240V, 5A, 50-60Hz
Mechanical features	L x H x D	483mm x 177mm (4U) x 485mm D 525mm including handles
	Weight	15 Kg for medium configuration
	Internal bay	2 x 3"½ unit
	External bay	3 x 5"¼ unit 1 x 3"½ unit
Software	Colour	Black
	Supported operating system	Microsoft Windows 10 64bit
Environment	Operating temp.	From +5°C to +35°C
	Non operating temp.	From -20°C to +70°C
	RH	95% @ 30°C non cond.
Product certifications	Reference Marks	CE, RoHS
	Directive	Built according to EU Directive 2014/30/EU(EMCD), 2014/35/EU(LVD) and 2011/65/EU(RoHS)
Company certifications	Reference standards	UNI EN ISO 9001
Product code	CNC698N7IN0	CORA 4000 Intel X150, DDR4, Gb Lan+SATA3 Raid, USB 2.0/3.0



Intercomp S.p.A.

Via della Scienza 27, 37139, Verona, Italia
Tel +39 045-8378411 Fax +39 045-8510539
www.intercomp.it intercomp@intercomp.it

The product may differ from the images shown. All registered names and trademarks are legitimate owners. All features and specifications can be changed without prior notice.
Last update 10/12/2018