














IDAS 2000 C236

Rackmount Server



- ✓ Ideal server for small and medium-sized businesses.
- ✓ Single sockets for Intel® Xeon® Processor E3-1200v6 or v5 Family
- ✓ Up to 64GB DDR4 ECC RAM
- ✓ Up to 12 Hot Swap HDD/SSD
- ✓ Dual Intel® Gigabit LAN
- ✓ Redundant power supply

NON  24/7 STOP	Intel® Xeon®  E3-1200v6 & v5	DDR4 ECC  UP TO 64 GB	Integrated SATA RAID CTRL  RAID 0,1,10	REDUNDANT  800W PSU	RACKMOUNT 19" ↔ 2U ↑↓	 2 x Gb LAN
Management  iAMT 11.0	 PCI EXPRESS 3.0	Rear USB  3.0 / 2.0	COM  RS232	 +5~+35°C	 RoHS	 CE

IDAS 2000 C236

Rackmount Server



System	Processor	Single sockets for Intel® Xeon® Processor E3-1200v6 and v5 Family
	Chipset	Intel® C236 Platform Controller Hub (PCH) chipset
	Slot di espansione	1 x PCI Express 3.0 x8 (x16 mechanical) 1 x PCI Express 3.0 x8 (x8 mechanical) 1 x PCI Express 3.0 x4 (x8 mechanical)
Memory	Max expansion.	64GB
	Type	DDR4-2133 ECC Unbuffered DIMM
	Slot	4
	Note	System equipped with 2 memory channels, each channel supports 2 ECC U-DIMM modules. For maximum performance it's recommended to use 2 or 4 memory modules. To guarantee maximum compatibility with the system, it's preferable to use identical memory modules.
Front I/O interfaces	USB	2 x USB 2.0
Rear I/O interfaces	USB	2 x USB 3.0 2 x USB 2.0 2 x USB 3.0 optional
	LAN	3 x RJ45 (2xLAN 1xBMC)
	Video	1 x VGA D-Sub 15pin 1 x Display Port (only with Intel® Xeon® with integrated graphics)
	Serial	1 x RS232 optional
	USB	1 x USB 2.0 type A
Internal I/O interfaces	USB	1 x USB 2.0 type A
Storage	SATA controller	8 x SATA3 6.0 Gb/s Intel® ESRT2 RAID 0, 1, 10
	HDD/SSD bay	12 x External HotSwap HDD/SSD SATA 2.5"/3.5"
Video subsystem	Integrated video adapter	BMC integrated graphics with 2D hardware accelerator (16MB DDR3)
Network interfaces	Integrated network adapter	2 x 10/100/1000 (Intel® Ethernet Controller i210)
	Management	1 x BMC with IPMI 2.0 Optional KVM and media redirection with Intel® RMM4 key (AXXRMM4LITE)

Power	Standard PSU	Redundant 800W ATX ACTIVE PFC AC INPUT:100-240V 50-60Hz 10A-4A
Chassis features	L x H x D	437mm x 89mm x 648mm
	Weight	Estimate 30Kg for medium configuration
	Internal bay	N/A
	External bay	12 x HotSwap 3.5"
	Colour	Black
	Fixing	1 x Rack guides
Software	Supported operating system	Microsoft Windows Server 2016
Environment	Operating temp.	From + 5°C to + 35°C
	Non operating temp.	From -20°C to +70°C
	RH	95% @ 30°C not cond.
Product certifications	Reference marks	CE, RoHS
	Directive	Built according to the European directive 2014/30/EU (EMCD), 2014/35/EU (LVD) and 2011/65/EU (RoHS)
Company certifications	Reference standards	UNI EN ISO 9001:2015
Product code (base config)	CN2475N8X40	IDAS2000 Mono Xeon E3-1200 series, Intel C236, 12*HDD, Alim. Ridondante



Intercomp S.p.A.

Via della Scienza 27, 37139, Verona, Italia
Tel +39 045-8378411 Fax +39 045-8510539
www.intercomp.it intercomp@intercomp.it

The product may differ from the images shown. All registered names and trademarks are legitimate owners. All features and specifications can be changed without prior notice.
Last update 10/12/2016