














## IDAS 4000 C236

Rackmount Server



- ✓ Ideal server for small and medium-sized businesses.
- ✓ Single sockets for Intel® Xeon® Processor E3-1200v6 or v5 Family
- ✓ Up to 64GB DDR4 ECC RAM
- ✓ Up to 8 Hot Swap HDD/SSD
- ✓ Dual Intel® Gigabit LAN
- ✓ Redundant power supply

<b>NON</b>  <b>24/7</b> <b>STOP</b>	<b>Intel® Xeon®</b>  E3-1200v6 & v5	<b>DDR4 ECC</b>  UP TO <b>64 GB</b>	<b>Integrated SATA RAID CTRL</b>  RAID 0,1,10	<b>REDUNDANT</b>  <b>800W PSU</b>	<b>RACKMOUNT</b> <b>19"</b> ↔ <b>4U</b> ↑↓	 <b>2 x Gb LAN</b>
<b>Management</b>  <b>iAMT 11.0</b>	 <b>PCI EXPRESS</b> <b>3.0</b>	<b>Rear USB</b>  <b>3.0 / 2.0</b>	<b>COM</b>  <b>RS232</b>	 <b>+5~+35°C</b>	 <b>RoHS</b>	

# IDAS 4000 C236

Rackmount Server



<b>System</b>	<b>Processor</b>	Single sockets for Intel® Xeon® Processor E3-1200v6 and v5 Family
	<b>Chipset</b>	Intel® C236 Platform Controller Hub (PCH) chipset
	<b>Slot di espansione</b>	1 x PCI Express 3.0 x8 (x16 mechanical) 1 x PCI Express 3.0 x8 (x8 mechanical) 1 x PCI Express 3.0 x4 (x8 mechanical)
<b>Memory</b>	<b>Max expansion.</b>	64GB
	<b>Type</b>	DDR4-2133 ECC Unbuffered DIMM
	<b>Slot</b>	4
	<b>Note</b>	System equipped with 2 memory channels, each channel supports 2 ECC U-DIMM modules. For maximum performance it's recommended to use 2 or 4 memory modules. To guarantee maximum compatibility with the system, it's preferable to use identical memory modules.
<b>Front I/O interfaces</b>	<b>USB</b>	2 x USB 2.0
<b>Rear I/O interfaces</b>	<b>USB</b>	2 x USB 3.0 2 x USB 2.0 2 x USB 3.0 optional
	<b>LAN</b>	3 x RJ45 (2xLAN 1xBMC)
	<b>Video</b>	1 x VGA D-Sub 15pin 1 x Display Port (only with Intel® Xeon® with integrated graphics)
	<b>Serial</b>	1 x RS232 optional
<b>Internal I/O interfaces</b>	<b>USB</b>	1 x USB 2.0 type A
<b>Storage</b>	<b>SATA controller</b>	8 x SATA3 6.0 Gb/s Intel® ESRT2 RAID 0, 1, 10
	<b>HDD/SSD bay</b>	8 x External HotSwap HDD/SSD SATA 2.5"/3.5"
	<b>ODD bay</b>	3 x External 5.25"
<b>Video subsystem</b>	<b>Integrated video adapter</b>	BMC integrated graphics with 2D hardware accelerator (16MB DDR3)
<b>Network interfaces</b>	<b>Integrated network adapter</b>	2 x 10/100/1000 (Intel® Ethernet Controller i210)
	<b>Management</b>	1 x BMC with IPMI 2.0 Optional KVM and media redirection with Intel® RMM4 key (AXXRMM4LITE)

<b>Power</b>	<b>Standard PSU</b>	Redundant 800W ATX ACTIVE PFC AC INPUT:100-240V 50-60Hz 10A-4A
	<b>Chassis features</b>	
<b>Chassis features</b>	<b>L x H x D</b>	437mm x 178mm x 648mm
	<b>Weight</b>	Estimate 30.5Kg for medium configuration
	<b>Internal bay</b>	N/A
	<b>External bay</b>	8 x HotSwap 3.5" 3 x Slim 5.25"
	<b>Colour</b>	Black
	<b>Cooling</b>	3 x 5000 RPM Hot-Swappable / Front 2 x 5000 RPM Hot-Swappable / Rear
	<b>Fixing</b>	1 x Rack guides
<b>Software</b>	<b>Supported operating system</b>	Microsoft Windows Server 2016
<b>Environment</b>	<b>Operating temp.</b>	From + 5°C to + 35°C
	<b>Non operating temp.</b>	From -20°C to +70°C
	<b>RH</b>	95% @ 30°C not cond.
<b>Product certifications</b>	<b>Reference marks</b>	CE, RoHS
	<b>Directive</b>	Built according to the European directive 2014/30/EU (EMCD), 2014/35/EU (LVD) and 2011/65/EU (RoHS)
<b>Company certifications</b>	<b>Reference standards</b>	UNI EN ISO 9001:2015
<b>Product code</b> (base config)	<b>CN1D75N8X40</b>	IDAS4000 Mono Xeon E3-1200 series, Intel C236, 8*HDD, Alim. Ridondante



**Intercomp S.p.A.**  
Via della Scienza 27, 37139, Verona, Italia  
Tel +39 045-8378411 Fax +39 045-8510539  
www.intercomp.it intercomp@intercomp.it

The product may differ from the images shown. All registered names and trademarks are legitimate owners. All features and specifications can be changed without prior notice.  
Last update 10/12/2018