




DT13 H310

Small Factor Client



- ✓ Ideal in all home & office contexts where space is a prerogative.
- ✓ Up to 9th generation Intel® Core™ processor
- ✓ Up to 32GB of DDR4 memory
- ✓ Intel® HD graphics with up to 2 simultaneous displays
- ✓ 4K Display support
- ✓ Built-in High Definition Audio 2/4/5.1/7.1-channel
- ✓ It can be placed horizontally, vertically, and ready for mounting on VESA standard supports.



DT13 H310

Small Factor Client



System	Processor	Socket LGA 1151 Intel® Core™ 9 th & 8 th gen. Intel® Core™ i7 / Core™ i5 / Core™ i3 / Pentium TDP max. 65W	
	Chipset	Intel® H310 Express Chipset	
	BIOS	1 x 128 Mbit AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0	
	Expansion slots	1 x PCI Express 3.0 x16 low profile / half size	
Memory	Max exp.	32GB	
	Type	DDR4- 2666/2400/2133 UDIMM 288pin 4GB, 8GB, 16GB	
	Slots	2	
Front I/O Interfaces	Audio	1 x Jack 3.5mm headphone 1 x Jack 3.5mm microphone	
	USB	2 x USB 2.0	
	Back I/O interfaces	Serial 1 x RS232 optional	
Back I/O interfaces	USB	2 x USB 2.0 2 x USB 3.1 gen.1	
	Keyboard/Mouse	2 x PS/2	
	Audio	3 x Jack 3.5mm (Line In, Line Out, Mic In)	
	LAN	1 x RJ45	
	Video	1 x VGA DB15 1 x DVI-D 1 x HDMI	
	Storage	Integrated SATA ctrl	4 x SATA 3 6Gb/s
		HDD/SSD bay	1 x *HDD/SSD SATA 2.5"
		ODD bay	1 x Slim ODD optional
Note		* Check the installed basic model and the available options on the web configurator	
Graphics subsystem	Integrated video interfaces	Intel® HD Graphics (depends on the CPU model) Max shared memory : 1GB	
	Max resolution	VGA DB15 : 1920x1200@60Hz DVI-D : 1920x1200@60Hz HDMI 1.4 : 4096x2160@30Hz (HDCP 2.2 support)	
	Contemporary active displays	Max 2	
	Audio subsystem	Integrated audio interfaces	Intel® HD Audio (codec Realtek® ALC887)
Channel		2 / 4 / 5.1 / 7.1 The HDMI 1.4 port carries the audio signal	

Network subsystem	Integrated network controller	1 x 10/100/1000 Realtek® GbE LAN
	Power	Standard PSU 250W ACTIVE PFC - 80Plus Bronze (85+) AC INPUT 100-240V, 4-2A, 50-60Hz
Mechanical features	W x H x D	254mm x 88mm x 219mm
	Weight	5 Kg for medium configuration
	Internal bay	1 x 2" ½ unit
	External bay	1 x Slim 5" ¼ unit
	Colour	Black
Software	Supported operating system	Microsoft Windows 10 64bit
Environment	Operating temp.	From +5°C to + 35°C
	Non op. temp.	From -20°C to +70°C
	RH	95% @ 30°C non cond.
Product certifications	Reference marks	CE, RoHS
	Directives	Built according to European Directive 2014/30/EU (EMCD), 2014/35/EU (LVD) and 2011/65/EU (RoHS)
Company	Reference standard	UNI EN ISO 9001
Product code	CNPCDT13-19-xxA	Explorer DT13, Intel H310, DDR4



Intercomp S.p.A.
Via della Scienza 27, 37139, Verona, Italia
Tel +39 045-8378411 Fax +39 045-8510539
www.intercomp.it intercomp@intercomp.it

Scan me

The product may differ from the images shown. All registered names and trademarks are legitimate owners. All features and specifications can be changed without prior notice.
Last update 15/01/2020