


MT14 H410

Client



- ✓ Ideal in all home & office contexts.
- ✓ 10th generation Intel® Core™ processor
- ✓ Intel® HD graphics with up to 2 simultaneous displays
- ✓ Support for dedicated PCI Express 3.0 x16 video cards
- ✓ Ultra-Fast M.2 with PCIe x2 & SATA interface
- ✓ Built-in High Definition Audio 2/4/5.1/7.1-channel



MT14 H410

Client



System	Processor	Socket LGA 1200 Intel® Core™ 10 th gen. Intel® Core™ i9 / i7 / i5 / i3 / Pentium	
	Chipset	Intel® H410 Express Chipset	
	BIOS	1 x 128 Mb AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0	
	Expansion slots	1 x PCI Express 3.0 x16 2 x PCI Express 2.0 x1 Supports up to ASPM L1.2 power management protocols.	
	Memory	Max exp.	64GB
Type		DDR4- 2933/2666/2400/2133 UDIMM 288pin 4GB, 8GB, 16GB, 32GB	
Slots		2	
Front I/O Interfaces	Audio	1 x Jack 3.5mm headphone 1 x Jack 3.5mm microphone	
	USB	2 x USB 3.2 gen.1	
Back I/O interfaces	Serial	1 x RS232 (optional)	
	LPT	N/A	
	USB		4 x USB 2.0 2 x USB 3.2 gen.1 2 x USB 2.0 optional
		Keyboard/Mouse	2 x PS/2
		Audio	3 x Jack 3.5mm (Line In, Line Out, Mic In)
	LAN	1 x RJ45	
	Video		1 x VGA DB15 1 x DVI-D 1 x HDMI
		Integrated SATA ctrl	4 x SATA 3 6Gb/s 1 x M.2 (Socket 3, M key, 2242/2260/2280 SATA and PCIe x2 SSD)
		Card Reader	Optional
	Storage	Internal bay	1 x *HDD/SSD SATA 3.5" unit
External bay		1 x *ODD 5" ¼ unit	
Graphics subsystem	Note	* Check the installed basic model and the available options on the web configurator	
	Integrated video interfaces	Intel® HD Graphics (depends on the CPU model) Max shared memory : 512MB	
	Max resolution	VGA DB15 : 1920x1200@60Hz DVI-D : 1920x1200@60Hz HDMI 1.4 : 4096x2160@30Hz (HDCP 2.3 support)	
	Contemporary active displays	Max 2	
	Audio subsystem	Integrated audio interfaces	Intel® HD Audio (codec Realtek® ALC887)
Channel		2 / 4 / 5.1 / 7.1 The HDMI 1.4 port carries the audio signal	

Network subsystem	Integrated network controller	1 x 10/100/1000 Realtek® GbE LAN
	Power	Standard PSU 500W ATX ACTIVE PFC AC INPUT:200-240V, 4A, 50-60Hz
Mechanical features	L x A x P	170mm x 365mm x 405mm
	Weight	7 Kg for medium configuration
	Internal bay	1 x 3" ½ unit
	External bay	1 x 5" ¼ unit 1 x 3" ½ unit
Software	Colour	Black
	Supported operating system	Microsoft Windows 10 64bit
Environment	Operating temp.	From +5°C to + 35°C
	Non op. temp.	From -20°C to +70°C
	RH	95% @ 30°C non cond.
Product certifications	Reference marks	CE, RoHS
	Directives	Built according to European Directive 2014/30/EU (EMCD), 2014/35/EU (LVD) and 2011/65/EU (RoHS)
Company	Reference standard	UNI EN ISO 9001
Product code	CNMGACNEINO	MT14 Intel H470, Gb Lan+SATA3 Raid, USB 2.0/3.0
	Doc ref.	ZST-4292-00000084-00



Scan me



Intercomp S.p.A.
Via della Scienza 27, 37139, Verona, Italia
Tel +39 045-8378411 Fax +39 045-8510539
www.intercomp.it intercomp@intercomp.it



The product may differ from the images shown. All registered names and trademarks are legitimate owners. All features and specifications can be changed without prior notice.
Last update 14/12/2020