

## MT20 C246

Compact Server



- ✓ Ideal server for small sized businesses.
- ✓ Intel® Xeon® E Processor
- ✓ Up to 128GB DDR4 ECC RAM
- ✓ Support for PCI Express 3.0 cards
- ✓ Built-in Intel® VROC RAID 6-channel SATA Controller, up to 6Gb/s
- ✓ Optional PCIe RAID controller Broadcom (LSI) MegaRAID® SAS/SATA
- ✓ Up to 5 internal HDD/SSD
- ✓ 4 Intel® Gigabit LAN
- ✓ 1 Intel® Gigabit LAN dedicated for management, IPMI 2.0 compliant



# MT20 C246

Compact Server



<b>System</b>	<b>Processor</b>	Socket LGA 1151 Intel® Xeon® E-2xxx Processor TDP up to 95W	
	<b>Chipset</b>	Intel® C246	
	<b>BIOS</b>	1 x 256 Mb AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0	
	<b>Expansion slots</b>	1 x PCI Express 3.0 x8 (mechanical x16) 1 x PCI Express 3.0 x8 (mechanical x8) 1 x PCI Express 3.0 x4 (mechanical x8)	
<b>Memory</b>	<b>Max exp.</b>	128GB	
	<b>Type</b>	DDR4- 2666 UDIMM 288pin 4GB, 8GB, 16GB, 32GB	
	<b>Slots</b>	4	
<b>Front</b>	<b>Audio</b>	N/A Only chassis mechanical predisposition for: 2 x Jack 3.5mm	
<b>I/O Interfaces</b>	<b>USB</b>	2 x USB 3.2 Type A Only chassis mechanical predisposition for: 2 x USB 2.0 Type A 1 x USB 2.0 Type C	
	<b>Serial</b>	2 x RS232 (optional)	
<b>Back I/O interfaces</b>	<b>LPT</b>	N/A	
	<b>USB</b>	4 x USB 3.1 Type A	
	<b>Audio</b>	N/A	
	<b>LAN</b>	5 x RJ45	
	<b>Video</b>	1 x VGA DB15 2 x DP (Display Port)	
<b>Storage</b>	<b>Integrated SATA ctrl</b>	6 x SATA 3 6Gb/s 2 x SATA-DOM ports Intel® VROC SATA RAID Support for RAID 0, RAID 1, RAID 5, and RAID 10	
	<b>SAS PCIe x8 Controller (optional)</b>	LSI MegaRAID® SAS 9341-4i 4 x 12Gb/s SAS/SATA RAID 0, 1, 5, 10, 50 & JBOD mode	
	<b>Internal bay</b>	4 x *HDD/SSD SATA 3.5" unit 1 x *HDD/SSD SATA 2.5" or 3.5" unit	
	<b>External bay</b>	3 x *ODD 5.25" unit	
	<b>Note</b>	* Check the installed basic model and the available options on the web configurator	
	<b>Graphics subsystem</b>	<b>Integrated video interfaces</b>	Integrated 2D video controller 16MB DDR4 video memory
	<b>Management</b>	<b>Server management</b>	Integrated BMC, IPMI 2.0 compliant Dedicated lan port Shared management interface
<b>Security</b>		Optional TPM module	

<b>Network subsystem</b>	<b>Integrated network controller</b>	4 x 10/100/1000 Intel® GbE LAN
	<b>Management</b>	1 x 10/100/1000 Intel® GbE LAN
<b>Power</b>	<b>Standard PSU</b>	550W ATX ACTIVE PFC, 80Plus Bronze (85+) AC INPUT 200-240V, 4A, 50-60Hz
	<b>L x A x P</b>	185mm x 420mm x 450mm
<b>Mechanical features</b>	<b>Weight</b>	7.5 Kg for medium configuration
	<b>Internal bay</b>	4 x 3.5" unit 1 x 2.5" or 3.5" unit
	<b>External bay</b>	3 x 5.25" unit 1 x 3.5" unit
<b>Software Environment</b>	<b>Colour</b>	Black
	<b>Supported O.S.</b>	Windows Server 2019
<b>Product certifications</b>	<b>Operating temp.</b>	From +5°C to + 35°C
	<b>Non op. temp.</b>	From -20°C to +70°C
	<b>RH</b>	95% @ 30°C non cond.
<b>Company Product code</b>	<b>Reference marks</b>	CE, RoHS
	<b>Directives</b>	Built according to European Directive 2014/30/EU (EMCD), 2014/35/EU (LVD) and 2011/65/EU (RoHS)
<b>Product code</b>	<b>Reference standard</b>	UNI EN ISO 9001
	<b>CNUNADNFINO</b>	MT20 Mono Xeon E-2000 series, Intel C246, 4xGb Lan+SATA3 6Gb/s Raid
	<b>Doc ref.</b>	ZST-4292-00000100-00



**Intercomp S.p.A.**  
Via della Scienza 27, 37139, Verona, Italia  
Tel +39 045-8378411 Fax +39 045-8510539  
www.intercomp.it intercomp@intercomp.it

Scan me

The product may differ from the images shown. All registered names and trademarks are legitimate owners. All features and specifications can be changed without prior notice.  
Last update 11/02/2021