





Challenger-R2 C246

Rackmount & tower server



- ✓ Ideal server for small sized businesses.
- ✓ Intel® Xeon® E Processor
- ✓ Up to 128GB DDR4 ECC RAM
- ✓ Support for PCI Express 3.0 cards
- ✓ Built-in Intel® VROC RAID 6-channel SATA Controller, up to 6Gb/s
- ✓ Optional PCIe RAID controller Broadcom (LSI) MegaRAID® SAS/SATA
- ✓ Up to 8 internal HDD/SSD
- ✓ 4 Intel® Gigabit LAN
- ✓ 1 Intel® Gigabit LAN dedicated for management, IPMI 2.0 compliant



Challenger-R2 C246

Rackmount & tower server



System	Processor	Socket LGA 1151 Intel® Xeon® E-2xxx Processor TDP up to 95W
	Chipset	Intel® C246
	BIOS	1 x 256 Mb AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
	Expansion slots*	1 x PCI Express 3.0 x8 (mechanical x16) 1 x PCI Express 3.0 x8 (mechanical x8) 1 x PCI Express 3.0 x4 (mechanical x8)
	Note	*One used, when SAS RAID controller is present
Memory	Max exp.	128GB
	Type	DDR4- 2666 UDIMM 288pin 4GB, 8GB, 16GB, 32GB
	Slots	4
Front I/O interfaces	USB	2 x USB 3.1 Gen.1 2 x USB 2.0 (Disabled / Only predisposition)
	Audio	2 x Jack 3.5mm (Disabled / Only predisposition)
Rear I/O interfaces	Serial	2 x RS232 (optional)
	LPT	N/A
	USB	4 x USB 3.1 Gen.2 Type A
	Audio	N/A
	LAN	5 x RJ45
	Video	1 x VGA DB15 2 x DP (Display Port)
	Storage	SATA controller
	PCIe SAS controller *can be optional	LSI MegaRAID® SAS 12Gb/s SAS/SATA **4 or 8 channels, RAID 0, 1, 5, 10, 50, JBOD Optional: CacheVault Flash Cache Protection Module
	HDD/SSD bay	4 x 3.5" (can be 2.5" with optional adapter) 4 x 2.5"
	ODD bay	2 x External 5.25"
	Other	1 x External 3.5"
	Note	*Optional in "Challenger-R2 SATA" configuration **See web configurator for available options.
Video subsystem	Integrated video interfaces	Integrated 2D video controller 16MB DDR4 video memory
Management	Server management	Integrated BMC, IPMI 2.0 compliant Dedicated lan port Shared management interface
	Security	Optional TPM module
Network interfaces	Integrated network controller	4 x 10/100/1000 Intel® GbE LAN
	Management	1 x 10/100/1000 Intel® GbE LAN

Power	Standard PSU	900W ATX Active PFC, 80Plus Gold, AC INPUT:100-240V, 50-60Hz
Chassis features	L x H x D	193mm x 424mm x 525mm
	Weight	Estimate 19Kg for medium configuration
	Internal bay	4 x 3.5" (can be 2.5" with optional adapter) 4 x 2.5"
	External bay	2 x 5.25" 1 x 3.5"
	Colour	Black
	Placing	Tower/Desktop
Software	Supported operating system	Microsoft Windows Server 2019
Environment	Operating temp.	From + 5°C to + 35°C
	Non operating temp.	From -20°C to +70°C
	RH	90% @ 30°C not cond.
Product certifications	Reference marks	CE, RoHS
	Directive	Built according to the European directive 2014/30/EU (EMCD), 2014/35/EU (LVD) and 2011/65/EU (RoHS)
Company certifications	Reference standards	UNI EN ISO 9001
Product code (base)	CNT7AGNFINO	CHALLENGER-R2 Mono Xeon E-2000 series, Intel C246, 4xGb Lan+SATA3 6Gb/s Raid
	Doc ref.	ZST-4292-00000111-00





 Scan me

Intercomp S.p.A.
 Via della Scienza 27, 37139, Verona, Italia
 Tel +39 045-8378411 Fax +39 045-8510539
www.intercomp.it intercomp@intercomp.it

The product may differ from the images shown. All registered names and trademarks are legitimate owners. All features and specifications can be changed without prior notice.
 Last update 23/03/2021