

Flex24 H410T

Emotional PC



- ✓ Ideal in all home & office contexts
- ✓ Up to 10th generation Intel® Core™ processor
- ✓ Intel® HD graphics with up to 2 simultaneous displays
- ✓ Display 24" Full HD
- ✓ Projected capacitive touchscreen, up to 10 touch points
- ✓ Up to 64GB RAM
- ✓ Gigabit LAN
- ✓ Bluetooth 4.x & WiFi 802.11ac





Technical features

System	Processor	Socket LGA 1200 Intel® Core™ 10 th gen. Intel® Core™ i7 / i5 / i3 / Pentium, TDP up to 65W	
	Chipset	Intel® H410 Express Chipset	
	BIOS	128 Mb Flash ROM, UEFI AMI BIOS, PnP, DMI 3.0, WfM 2.0, SM BIOS 3.1, ACPI 6.1	
	Expansion slot	1 x M.2 M key, 2280/2260 storage (SATA & PCIe x2 mode) 1 x M.2 E key, 2230 Wi-Fi/BT (PCIe, CNVi/USB mode)	
Memory	Max expansion	64GB	
	Type	DDR4 2933/2666/2400/2133 SO-DIMM 4GB, 8GB, 16GB, 32GB	
	Slot	2	
Side DX I/O interfaces	USB	2 x USB 2.0	
Side SX I/O interfaces	USB	2 x USB 3.2 Gen1 2 x USB 2.0	
	Audio	2 x Jack 3.5mm	
	LAN	1 x RJ45	
	Video	1 x DP (Display Port) 1 x HDMI	
	Power	1 x DC power connector	
	Storage	Integrated SATA controller	1 x M.2 (Socket 3, M key, 2280/2260 SATA & PCIe x4 SSD) 2 x SATA3 6Gb/s
		Card Reader	6 in 1 Card Reader SD/XD/MMC
HDD/SSD bay		1 x HDD/SSD SATA 3.5/2.5"	
ODD bay		1 x Slim DVD +R+RW-R-RW	
Graphics subsystem	Integrated video interface	Intel® HD Graphics*	
	Integrated LCD display	23.6" TFT LCD – Led Backlight Full HD 16:9 1920x1080	
	Max resolution (external ports)	HDMI 1.4b : 4096x2160@24Hz* DP 1.4 : 4096x2304@60Hz*	
	Contemporary active display	Max 2 (1 internal, 1 external)	
	Touchscreen	Touchscreen with projected capacitive technology, up to 10 touch points, USB interface	
	Note	*depends on installed processor	
	Multimedia	Webcam	Integrated in the front frame, 1.3Mpx
Microphone		Integrated in the front frame	

Audio subsystem	Integrated audio adapter	Realtek® ALC887 7.1 - Channel High Definition Audio
	Speaker	2 x 5W (integrated on the back)
Network subsystem	Integrated network adapter	1 x 10/100/1000 Realtek® RTL8111H GbE LAN
	WiFi & BT	Dual Band Wireless 802.11ac, Bluetooth 4.x
Power	External power supply	Input : 100-240V Output : 19V
Mechanical features	L x A x P	588mm x 443mm x 200mm (with support base) 588mm x 388mm x 53mm (without a support base)
	Placement	Desktop VESA 100 with optional kit
	Weight	6.5Kg (estimated for medium conf. excluding support base) 7.3Kg (estimated for medium conf. including support base)
	Internal bay	1 x 3" ½ or 2" ½ unit
	External bay	1 x slim 5" ¼ unit
	Color	White (back), Black (Front), Silver (sup. base)
	Supported operating system	Microsoft Windows 10 64bit
Software	Operating temp.	From + 5°C to + 35°C
	Non op. temp.	From -20°C to +70°C
	RH	95% @ 30°C non cond.
Environment	Reference Marks	CE, RoHS
	Directives	Build in conformity with European 2014/53/EU (RED) and 2011/65/EU (RoHS)
Product certifications	Reference standards	UNI EN ISO 9001
	Ordering code	CNPCAIOFL24-H410T-4x
Company certifications	Reference standards	PC "Flex24-410T" All-In-One 24" TOUCH, Intel H410, 1*GB Lan,WIFI+BT,Web
	Ordering code	CNPCAIOFL24-H410T-4x

Doc. Ref. ZST-4292-00000113-02



Intercomp S.p.A.

Via della Scienza 27, 37139, Verona, Italia
Tel +39 045-8378411 Fax +39 045-8510539
www.intercomp.it intercomp@intercomp.it

The product may differ from the images shown. All registered names and trademarks are legitimate owners. All features and specifications can be changed without prior notice.
Last update 01/03/2022